

# JSP1200 LITHIUM JUMP STARTER + POWER BANK



JUMP START UP TO  
8L PETROL ENGINE



IP66  
WATERPROOF



JUMP START UP TO  
6L DIESEL ENGINE



1200A  
PEAK CURRENT

The waterproof JSP1200 lithium jump starter has been designed as a portable roadside assistant, including the capability of jump starting a vehicle, convenient USB ports for smart device charging on the run.

**12** MONTH  
WARRANTY

LED TORCH PLUS CHARGING PORTS



CARRY CASE



[oricom.com.au](http://oricom.com.au)

Oricom® is the registered trade mark of Oricom Holdings Pty Ltd.  
All other trade marks are trade marks of their respective owners.

**oricom**  
100% AUSSIE OWNED

# JSP1200 LITHIUM JUMP STARTER + POWER BANK

 JUMP START UP TO  
8L PETROL ENGINE

 IP66  
WATERPROOF

 JUMP START UP TO  
6L DIESEL ENGINE

 1200A  
PEAK CURRENT



## JUMP STARTING YOUR CAR IS QUICK AND EASY



- 1 Insert the plug of the smart battery clamp into the jump starter. The green and red light indicators on the battery clamp will then flash alternately.
- 2 Connect the red clamp to the positive terminal (+) and the black clamp to the negative terminal (-) of the car battery.
- 3 Start your car.
- 4 Once your car has started, remove the battery clamps from the car battery within 30 seconds.

## KEY FEATURES

- Designed to jump start up to 8L petrol engines and up to 6L diesel engines
- Charge phones, tablets and all USB devices
- LED torch
- IP66 Water and dust proof
- Universal 12V clamps

## PACK CONTENTS

- 1 x JSP1200 Jump starter
- 1 x Smart battery clamp
- 1 x USB-A to USB-C cable
- 1 x USB-C to USB-C cable
- 1 x AC Charger
- 1 x 12V Car charger
- 1 x User manual
- 1 x Carry case

## TECHNICAL SPECIFICATION

Micro USB input	5V/2.1A
Torch	1W LED, 100 lumens
Type-C input & output	(PD30W) 5V/3A, 9V/3A, 12V/2.5A, 20V/1.5A, (QC18W) 5V/3A, 9V/2A, 12V/1.5A
Type-A USB output 1	5V/3A, 9V/2A, 12V/1.5A
Type-A USB output 2	5V/3A, 9V/2A, 12V/1.5A
Start current	600A (lasts for 1.5S) Start current 350A (lasts for 3S)
Peak current	1200A (lasts for 0.1S)
Battery capacity	59.2Wh
Short circuit protection	Effective
Over-discharge protection	≤13V±0.3V
Over-temperature protection	> 65°C±5°C
Reverse polarity protection	Effective
Reverse charging protection	≥(12.6V±0.3V)
Dimensions (L*W*H)	185*100*45mm
Waterproof rating	Ingress protection rating: IP66 Protection against powerful jets of water at 100kPa at 3m for 15 mins. Charge port cover must be in place.



**12** MONTH  
WARRANTY

[oricom.com.au](http://oricom.com.au)

Oricom® is the registered trade mark of Oricom Holdings Pty Ltd.  
All other trade marks are trade marks of their respective owners.

**oricom**  
100% AUSSIE OWNED